

Thermostatically controlled incubators - TC series

Standard or glass door - lockable



The TC series of thermostatically controlled cabinets is used for continuous temperature control over a range of 2 °C to 40 °C. This makes them ideal for a wide range of different applications in industrial and research laboratories.

In particular they are ideal for the temperature-controlled storage of samples or BOD determination in effluent analysis work.

The temperature can be set in steps of 0.1 °C and an LED display shows both the set temperature and the current temperature in the cabinets. Devices such as magnetic agitators, which require a power supply, can be connected to sockets incorporated in the interior of the cabinet.

The integral temperature control unit meets the requirements of the EMC directive issued as IEC 61326: "Electrical devices for measurement, monitoring and for use in laboratories".

Improved, robust, insulated housing and highly efficient components provide maximum energy efficiency.

There are 4 models available with standard doors from 135 to 445 litres net capacity, and 2 models with glass doors with 140 and 255 litres net capacity.

Highlights

- Temperature range 2 °C to 40 °C, continuously adjustable in steps of 0.1 °C
- Low power consumption
- Illuminated LED display of preset and current temperatures
- Ideal for BOD determination at 20 °C
- Power sockets inside the incubator
- 6 models in 4 sizes
- Standard door or glass door

Applications

- BOD-Measurement
- Microbiological Research
- Food Industry
- Dairies
- Laboratories
- Research Centres
- Universities

Models with standard door

TC 135 S

3 metal racks + 1 bottom grid + 4 sockets

Consumption: approx. 1.35 kWh / 24 h*

I. D. (approx.): 513 W x 441 D x 702 H mm

Net capacity: approx. 135 l

O. D. (approx.):

600 W x 600 D x 850 H mm with work top
600 W x 600 D x 819 H mm without work top

Suitable for built under applications

Weight: approx. 39.0 kg

Order code: 2 43 82 00

TC 175 S

3 metal racks + 1 bottom grid + 5 sockets

Consumption: approx. 1.23 kWh / 24 h*

I. D. (approx.): 470 W x 440 D x 1062 H mm

Net capacity: approx. 175 l

O. D. (approx.): 600 W x 610 D x 1250 H x mm

Weight: approx. 51.0 kg

Order code: 2 43 82 20

* Ambient temperature 25 °C

Target temperature 20 °C

Variations possible

Models with standard door

TC 255 S

4 metal racks + 1 bottom grid + 7 sockets

Consumption: approx. 1.54 kWh / 24 h*

I. D. (approx.): 470 W x 440 D x 1452 H mm

Net capacity: approx. 255 l

O. D. (approx.):

600 W x 610 D x 1640 H x mm

Weight: approx. 61.0 kg

Order code: 2 43 82 30

TC 445 S

4 metal racks + 1 bottom grid + 9 sockets

Consumption: approx. 1.42 kWh / 24 h*

I. D. (approx.): 600 W x 560 D x 1452 H mm

Net capacity: approx. 445 l

O. D. (approx.): 750 W x 730 D x 1640 H x mm

Weight: approx. 78.5 kg

Order code: 2 43 82 40

* Ambient temperature 25 °C

Target temperature 20 °C

Variations possible

Models with glass door

TC 140 G

3 metal racks + 1 bottom grid + 4 sockets

Consumption: approx. 1.77 kWh / 24 h**

I. D. (approx.): 513 W x 441 D x 702 H mm

Net capacity: approx. 140 l

O. D. (approx.):

600 W x 600 D x 850 H x mm with work top
600 W x 600 D x 819 H mm without work top

Suitable for built under applications

Weight: approx. 48.0 kg

Order code: 2 43 82 10

TC 256 G

4 metal racks + 1 bottom grid + 7 sockets

Consumption: approx. 1.56 kWh / 24 h**

I. D. (approx.): 470 W x 440 D x 1452 H mm

Net capacity: approx. 255 l

O. D. (approx.): 600 W x 610 D x 1640 H x mm

Weight: approx. 77.0 kg

Order code: 2 43 82 35

** Ambient temperature 25 °C

Target temperature 20 °C

with interior lighting switched on (15 W)
Variations possible

Technical Data

Design	Fully insulated cabinet with universal temperature control unit	Temperature tolerance	± 1 °C, specified for a stirred 500 ml water sample. For BOD (T=20 °C ±0,5 °C)
Lock	existing	Display	Backlit LED display Resolution 0.1 °C
Models with glass door	Insulating glass door in an ABS frame. ceiling lighting, separately switchable	Fan	Axial, output 320 m³/h
Operation	Splash-proofed keypad, 2 buttons with tactile feedback	Cooling/Heating	Integrated powerful cooling and heating
Control range	+ 2 °C to + 40 °C, steps of 0.1 °C	Power supply	220 - 240 V / 50 Hz
Climate class	+ 10 °C to + 32 °C,	Sockets	CEE 7/5, type E with hinged lid, 230 V / 16 A 2p + E, IP 44
		Coolant	R134a
		Approval	CE

Space for BD 600 systems

Model	Systems, standard ¹⁾	Systems, comfort ²⁾
TC 135 S / TC 140 G	3	2
TC 175 S	5	2
TC 255 S / TC 256 G	7	3
TC 445 S	12	9

¹⁾ Change of bottles **by** removing racks.

²⁾ Change of bottles **without** removing racks.

Temperature control unit

The temperature control unit fulfills the EMC requirements according IEC 61326 : Electrical equipment for measurement, control and laboratory use.

